digital™ MATERIAL SAFETY DATA SHEET

SECTION 1 - PREPARATION/PRODUCT INFORMATION

Manufacturer's Name: Digital Equipment Corporation, Maynard, MA USA

Non-Emergency Phone Number: (508) 496-9242

Emergency Phone Numbers: 800-228-5635 ext.123
[+1] 612-221-3999 ext.123

Preparation Date: September 15, 1992

Supersedes: July 9, 1990

Product Name: PrintServer Drum

Part Number(s): 29-27398-01, LPS2X-AC, LPS3X-AC

Use: Image Transfer Device for LPS20, LPS32 Printers

SECTION 2 - INGREDIENTS

HAZARDOUS INGREDIENTS	CAS	%	ACGIH TLV	OSHA PEL	CARCINOGEN LIST IARC	CARCINOGEN LIST NTP	CARCINOGEN LIST OSHA	SARA 313
None								

Drum is classified as an article. Drum coating contains titanium dioxide. See Section 8 for safe handling /preventive measures.

All ingredients in this product are on the U.S. TSCA inventory.

SECTION 3 - PHYSICAL AND CHEMICAL DATA

Boiling Point - Not applicable
Vapor Pressure - Not applicable
Vapor Density - Not applicable
Appearance - Green colored drum
Freezing Point - Not applicable
Melting/Softening Point - Not available
Solubility in Water - < 0.1%
Percent Volatile - None
Evaporation Rate - Not applicable
Odor and Odor Threshold - None
pH - Not applicable
Specific Gravity - Not applicable

SECTION 4 - FIRE AND EXPLOSION HAZARD

Flash Point - None
Auto-Ignition Temperature - Not applicable
Unusual Fire or Explosion Hazards - None
Hazardous Combustion Products - Carbon monoxide, carbon dioxide
Special Fire Fighting Procedure - None
Flammable Limits - None
Extinguishing Media - Water, foam, dry chemical, carbon dioxide

© Digital Equipment Corporation. 1992. All rights reserved.

SECTION 5 - REACTIVITY DATA

Stability - Stable
Incompatibility - Strong bases
Hazardous Decomposition Products - Not available
Conditions to Avoid - Temperature above 80°C (176°F)
Hazardous Polymerization -None

SECTION 6 - HEALTH HAZARD DATA/TOXICOLOGICAL PROPERTIES

Hazard to Humans- None during normal use. Exposure to the drum coating could occur if the drum coating was cracked or scratched. Inhalation of dust from coating may cause irritation of nose, throat, and lungs.
Animal Experiment- None
Additional Information- See Section 8 for safe handling/preventive measures. Drum coating contains titanium dioxide which is listed by SARA, OSHA and ACGIH as a hazardous chemical. It has an OSHA PEL of 10 mg/m^3.

SECTION 7 - EMERGENCY/FIRST AID PROCEDURE

(Applies to drum coating)

If Inhaled - Remove to fresh air. Support breathing if necessary and contact a physician.
If on Skin - Promptly wash skin with soap and water.
If in Eyes - Flush eyes with large quantities of water for at least 15 minutes.
If Swallowed- Seek immediate medical attention.

SECTION 8 - SAFE HANDLING/PREVENTIVE MEASURES

Personal Protective Equipment - None for normal use of drum.
Engineer Control - Not needed.
Waste Disposal - No special requirements.
Procedures for Leaks or Spills- Not applicable
Work Practices - None
Storage Requirement- Avoid temperatures >43°C (109°F).
Handling Procedure/Equipment- Handle drum carefully to avoid damaging coating.
Labelling- None
WHMIS Classification- Not applicable

SECTION 9 - TRANSPORTATION REQUIREMENTS

None